

Edition: August 2009

Publication No. SM0E-1S51U0



All rights reserved. No part of this Service Manual may be reproduced or stored in a retrieval system, or transmitted in any form, or by any means, electronic, mechanical, recording or otherwise, without the prior written permission of Nissan Motor Company Ltd.

QUICK REFERENCE INDEX

A GENERAL INFORMATION	GI General Information
B ENGINE	EM Engine Mechanical
	LU Engine Lubrication System
	CO Engine Cooling System
	EC Engine Control System
	FL Fuel System
	EX Exhaust System
	STR Starting System
ACC Accelerator Control System	
C HYBRID	
D TRANSMISSION & DRIVE-LINE	TM Transaxle & Transmission
	DLN Driveline
	FAX Front Axle
	RAX Rear Axle
E SUSPENSION	FSU Front Suspension
	RSU Rear Suspension
	SCS Suspension Control System
	WT Road Wheels & Tires
F BRAKES	BR Brake System
	PB Parking Brake System
	BRC Brake Control System
G STEERING	ST Steering System
	STC Steering Control System
H RESTRAINTS	SB Seat Belt
	SBC Seat Belt Control System
	SR SRS Airbag
	SRC SRS Airbag Control System
I VENTILATION, HEATER & AIR CONDITIONER	VTL Ventilation System
	HA Heater & Air Conditioning System
	HAC Heater & Air Conditioning Control System
J BODY INTERIOR	INT Interior
	IP Instrument Panel
	SE Seat
	ADP Automatic Drive Positioner
	DLK Door & Lock
K BODY EXTERIOR, DOORS, ROOF & VEHICLE SECURITY	SEC Security Control System
	GW Glass & Window System
	PWC Power Window Control System
	RF Roof
	EXT Exterior
	BRM Body Repair
	MIR Mirrors
L DRIVER CONTROLS	EXL Exterior Lighting System
	INL Interior Lighting System
	WW Wiper & Washer
	DEF Defogger
	HRN Horn
	PWO Power Outlet
	BCS Body Control System
M ELECTRICAL & POWER CONTROL	LAN LAN System
	PCS Power Control System
	CHG Charging System
	PG Power Supply, Ground & Circuit Elements
	MWI Meter, Warning Lamp & Indicator
N DRIVER INFORMATION & MULTIMEDIA	WCS Warning Chime System
	AV Audio, Visual & Navigation System
	CCS Cruise Control System
O CRUISE CONTROL	MA Maintenance
P MAINTENANCE	

A
B
D
E
F
G
H
I
J
K
L
M
N
O
P

FOREWORD

This manual contains maintenance and repair procedure for the 2010 INFINITI FX35/FX50.

In order to assure your safety and the efficient functioning of the vehicle, this manual should be read thoroughly. It is especially important that the PRECAUTIONS in the GI section be completely understood before starting any repair task.

All information in this manual is based on the latest product information at the time of publication. The right is reserved to make changes in specifications and methods at any time without notice.

IMPORTANT SAFETY NOTICE

The proper performance of service is essential for both the safety of the technician and the efficient functioning of the vehicle.

The service methods in this Service Manual are described in such a manner that the service may be performed safely and accurately. Service varies with the procedures used, the skills of the technician and the tools and parts available. Accordingly, anyone using service procedures, tools or parts which are not specifically recommended by NISSAN must first be completely satisfied that neither personal safety nor the vehicle's safety will be jeopardized by the service method selected.



INFINITI®

QUICK REFERENCE CHART FX35/FX50

PFP:00000

ENGINE TUNE-UP DATA (VQ35HR)

Engine model		VQ35HR
Firing order		1-2-3-4-5-6
Idle speed A/T (In "P" or "N" position)	rpm	675 ± 50
Ignition timing (BTDC at idle speed) A/T (In "P" or "N" position)		15° ± 5°
Tensions of drive belts		Auto adjustment by auto tensioner
Radiator cap relief pressure	kPa (kg/cm ² , psi)	
Standard		122.3 - 151.7 (1.2 - 1.5, 18 - 22)
Limit		107 (1.1, 16)
Cooling system leakage testing pressure	kPa (kg/cm ² , psi)	157 (1.6, 23)
Compression pressure	kPa (kg/cm ² , psi)/rpm	
Standard		1,275 (13.0, 185)/300
Minimum		981 (10.0, 142)/300
Spark plug	Standard type	FXE22HR11

ENGINE TUNE-UP DATA (VK50VE)

Engine model		VK50VE
Firing order		1-8-7-3-6-5-4-2
Idle speed A/T (In "P" or "N" position)	rpm	650 ± 50
Ignition timing (BTDC at idle speed) A/T (In "P" or "N" position)		15° ± 5°
Tensions of drive belts		Auto adjustment by auto tensioner
Radiator cap relief pressure	kPa (kg/cm ² , psi)	
Standard		122.3 - 151.7 (1.2 - 1.5, 18 - 22)
Limit		107 (1.1, 16)
Cooling system leakage testing pressure	kPa (kg/cm ² , psi)	157 (1.6, 23)
Compression pressure	kPa (kg/cm ² , psi)/rpm	
Standard		1,667 (17, 242)/200
Minimum		1,226 (12.5, 178)/200
Spark plug	Standard type	FXE22HR11

FRONT WHEEL ALIGNMENT (Unladen*)

Item		Standard	
Camber Degree minute (Decimal degree)	Minimum	-1° 05' (-1.08°)	
	Nominal	-0° 20' (-0.33°)	
	Maximum	0° 25' (0.41°)	
	Left and right difference	0° 33' (0.55°) or less	
Caster Degree minute (Decimal degree)	Minimum	2° 55' (2.92°)	
	Nominal	3° 40' (3.67°)	
	Maximum	4° 25' (4.41°)	
	Left and right difference	0° 39' (0.65°) or less	
Kingpin inclination Degree minute (Decimal degree)	Minimum	7° 55' (7.92°)	
	Nominal	8°40' (8.67°)	
	Maximum	9° 25' (9.41°)	
Toe-in	Total toe-in Distance	Minimum	In 1 mm (0.04 in)
		Nominal	In 2 mm (0.08 in)
		Maximum	In 3 mm (0.11 in)
	Toe angle (left wheel or right wheel) Degree minute (Decimal Degree)	Minimum	In 0° 02' 12" (0.04°)
		Nominal	In 0° 04' 24" (0.07°)
		Maximum	In 0° 06' 36" (0.11°)

Measure value under unladen* conditions.

*: Fuel, engine coolant and lubricant are full. Spare tire, jack, hand tools and mats are in designated positions.

AWD

Item		Standard	
Camber Degree minute (Decimal degree)	Minimum	-1° 05' (-1.08°)	
	Nominal	-0° 20' (-0.33°)	
	Maximum	0° 25' (0.41°)	
	Left and right difference	0° 33' (0.55°) or less	
Caster Degree minute (Decimal degree)	Minimum	2° 55' (2.92°)	
	Nominal	3° 40' (3.67°)	
	Maximum	4° 25' (4.41°)	
	Left and right difference	0° 39' (0.65°) or less	
Kingpin inclination Degree minute (Decimal degree)	Minimum	7° 55' (7.92°)	
	Nominal	8°40' (8.67°)	
	Maximum	9° 25' (9.41°)	
Toe-in	Total toe-in Distance	Minimum	In 1 mm (0.04 in)
		Nominal	In 2 mm (0.08 in)
		Maximum	In 3 mm (0.11 in)
	Toe angle (left wheel or right wheel) Degree minute (Decimal Degree)	Minimum	In 0° 02' 12" (0.04°)
		Nominal	In 0° 04' 24" (0.07°)
		Maximum	In 0° 06' 36" (0.11°)

Measure value under unladen* conditions.

*: Fuel, engine coolant and lubricant are full. Spare tire, jack, hand tools and mats are in designated positions.

REAR WHEEL ALIGNMENT (Unladen*)

Item		Standard			
Tire size		265/60R18	265/50R20	265/45R21	
Camber Degree minute (Decimal degree)	Minimum	-1° 40' (-1.66°)			
	Nominal	-1° 10' (-1.16°)			
	Maximum	-0° 40' (-0.67°)			
Toe-in	Total toe-in Distance	Minimum	0 mm (0 in)		
		Nominal	In 3.2 mm (0.126 in)	In 3.1 mm (0.122 in)	
		Maximum	In 6.4 mm (0.252 in)	In 6.2 mm (0.244 in)	
	Toe angle (left wheel or right wheel) Degree minute (Decimal Degree)	Minimum	0° 00' (0.00°)		
		Nominal	In 0° 07' (0.12°)		
		Maximum	In 0° 14' (0.23°)		

Measure value under unladen* conditions.

*: Fuel, engine coolant and lubricant are full. Spare tire, jack, hand tools and mats are in designated positions.

BRAKE

Front brake	Pad repair limit		2.0 mm (0.079 in)
	Rotor wear limit	2 piston type	32.0 mm (1.260 in)
		4 piston type	30.0 mm (1.181 in)
Rear brake	Pad repair limit		2.0 mm (0.079 in)
	Rotor wear limit	1 piston type	14.0 mm (0.551 in)
		2 piston type	18.0 mm (0.709 in)
Pedal free height	Without DCA		171.5 - 181.5 mm (6.75 - 7.15 in)
	With DCA		185.4 - 195.4 mm (7.30 - 7.69 in)
Pedal depressed height*	Without DCA		114.0 mm (4.49 in) or more
	With DCA		120.8 mm (4.76 in) or more

* : Under force of 490 N (50 kg, 110 lb) with engine running.

STEERING ANGLE

Unit: Degree minute (Decimal degree)

Item		Standard
Inner wheel	Minimum	38°00' (38.0°)
	Nominal	41°00' (41.0°)
	Maximum	42°00' (42.0°)
Outer wheel	Nominal	32°15' (32.3°)

REFILL CAPACITIES

UNIT		Liter	US measure
Fuel tank		90	23 - 3/4 gal
Coolant (With reservoir tank)	VQ35HR	9.2	9 - 3/4 qt
	VK50VE	11	11 - 5/8 qt
Engine (VQ35HR)	Drain and refill		
	With oil filter change		4.9
	Without oil filter change		4.6
Dry engine (Overhaul)		5.7	6 qt
Engine (VK50VE)	Drain and refill		
	With oil filter change		6.7
	Without oil filter change		5.8
Dry engine (Overhaul)		7.2	7 - 5/8 qt
Transmission	A/T	VQ35HR	9.2
		VK50VE	11.3
Transfer		1.0	2 - 1/8 pt
Differential gear	Front		0.65
	Rear	VQ35HR	1.4
		VK50VE	1.75
Power steering system		1.0	1 - 1/8 qt
Air conditioning system	Compressor oil		0.15
	Refrigerant		0.55 kg