

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
M  
N  
O  
P

# VSP

## SECTION

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP)

## CONTENTS

|  |    |   |    |
|--|----|---|----|
| <b>PRECAUTION</b> .....                                | 3  | <b>CHARGE SOUND SYSTEM</b> .....            | 19 |
| <b>PRECAUTIONS</b> .....                               | 3  | CHARGE SOUND SYSTEM : System Description... | 19 |
| Precaution for Technicians Using Medical Electric..... | 3  | <b>DIAGNOSIS SYSTEM (VSP)</b> .....         | 22 |
| Point to Be Checked Before Starting Maintenance        |    | CONSULT Function .....                      | 22 |
| Work .....   | 3  | <b>ECU DIAGNOSIS INFORMATION</b> .....      | 24 |
| Precaution for Supplemental Restraint System           |    | <b>APPROACHING VEHICLE SOUND FOR PE-</b>    |    |
| (SRS) "AIR BAG" and "SEAT BELT PRE-TEN-                |    | <b>DESTRIANS (VSP) CONTROL UNIT</b> .....   | 24 |
| SIONER" .....  | 3  | Reference Value .....                       | 24 |
| Precautions for Removing Battery Terminal .....        | 4  | Fail-Safe .....                             | 27 |
| <b>PREPARATION</b> .....                               | 6  | DTC Index .....                             | 27 |
| <b>PREPARATION</b> .....                               | 6  | <b>WIRING DIAGRAM</b> .....                 | 28 |
| Commercial Service Tools .....                         | 6  | <b>APPROACHING VEHICLE SOUND FOR PE-</b>    |    |
| <b>SYSTEM DESCRIPTION</b> .....                        | 7  | <b>DESTRIANS (VSP) SYSTEM</b> .....         | 28 |
| <b>COMPONENT PARTS</b> .....                           | 7  | Wiring Diagram .....                        | 28 |
| Component Parts Location .....                         | 7  | <b>BASIC INSPECTION</b> .....               | 29 |
| Approaching Vehicle Sound For Pedestrians              |    | <b>DIAGNOSIS AND REPAIR WORKFLOW</b> .....  | 29 |
| (VSP) Speaker .....                                    | 8  | Work Flow .....                             | 29 |
| Start Up Sound Speaker .....                           | 8  | <b>DTC/CIRCUIT DIAGNOSIS</b> .....          | 31 |
| Approaching Vehicle Sound For Pedestrians              |    | <b>U1431 COMM CIRCUIT</b> .....             | 31 |
| (VSP) Control Unit .....                               | 9  | Description .....                           | 31 |
| Approaching Vehicle Sound For Pedestrians              |    | DTC Logic .....                             | 31 |
| (VSP) Warning Lamp .....                               | 9  | Diagnosis Procedure .....                   | 31 |
| <b>SYSTEM</b> .....                                    | 10 | <b>POWER SUPPLY AND GROUND CIRCUIT</b> .... | 33 |
| System Description .....                               | 10 | <b>APPROACHING VEHICLE SOUND FOR PEDES-</b> |    |
| Circuit Diagram .....                                  | 11 | <b>TRIANS (VSP) CONTROL UNIT</b> .....      | 33 |
| Fail-Safe .....  | 11 | APPROACHING VEHICLE SOUND FOR PE-           |    |
| <b>START UP SOUND SYSTEM</b> .....                     | 12 | DESTRIANS (VSP) CONTROL UNIT : Diagnosis    |    |
| START UP SOUND SYSTEM : System Descrip-                |    | Procedure .....                             | 33 |
| tion .....   | 12 | <b>APPROACHING VEHICLE SOUND FOR PE-</b>    |    |
| <b>APPROACHING VEHICLE SOUND FOR PEDES-</b>            |    | <b>DESTRIANS (VSP) SPEAKER SIGNAL CIR-</b>  |    |
| <b>TRIANS(VSP) SYSTEM</b> .....                        | 14 | <b>CIRCUIT</b> .....                        | 34 |
| APPROACHING VEHICLE SOUND FOR PE-                      |    |   |    |
| DESTRIANS(VSP) SYSTEM : System Descrip-                |    |   |    |
| tion .....   | 14 |   |    |

VSP

|   |           |   |           |
|---|-----------|---|-----------|
| Description .....   | 34        | <b>THE APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SPEAKER DOES NOT SOUND .....</b> | <b>49</b> |
| Component Function Check .....  | 34        | Description .....   | 49        |
| Diagnosis Procedure .....   | 34        | Diagnosis Procedure .....   | 49        |
| <b>START UP SOUND SPEAKER SIGNAL CIRCUIT .....</b>  | <b>36</b> | <b>THE START UP SOUND SPEAKER DOES NOT SOUND .....</b>                                  | <b>50</b> |
| Description .....   | 36        | Description .....   | 50        |
| Component Function Check .....  | 36        | Diagnosis Procedure .....   | 50        |
| Diagnosis Procedure .....   | 36        | <b>THE CHARGE SOUND DOES NOT SOUND ...</b>  | <b>51</b> |
| <b>APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) WARNING LAMP SIGNAL CIRCUIT .....</b>              | <b>38</b> | Description .....   | 51        |
| Description .....   | 38        | Diagnosis Procedure .....   | 51        |
| Component Function Check .....  | 38        | <b>THE POWER SWITCH OPERATION SOUND DOES NOT SOUND .....</b>                            | <b>52</b> |
| Diagnosis Procedure .....   | 38        | Description .....   | 52        |
| <b>STOP LAMP SWITCH SIGNAL CIRCUIT .....</b>  | <b>40</b> | Diagnosis Procedure .....   | 52        |
| Description .....   | 40        | <b>NORMAL OPERATING CONDITION .....</b>   | <b>53</b> |
| Component Function Check .....  | 40        | <b>APPROACHING VEHICLE SOUND FOR PEDESTRIANS(VSP) SYSTEM .....</b>                      | <b>53</b> |
| Diagnosis Procedure .....   | 40        | APPROACHING VEHICLE SOUND FOR PEDESTRIANS(VSP) SYSTEM : Description .....               | 53        |
| Component Inspection .....  | 41        | <b>START UP SOUND SYSTEM .....</b>  | <b>53</b> |
| <b>CHARGE PULSE SIGNAL CIRCUIT .....</b>  | <b>42</b> | START UP SOUND SYSTEM : Description .....   | 53        |
| Description .....   | 42        | <b>CHARGE SOUND SYSTEM .....</b>  | <b>53</b> |
| Component Function Check .....  | 42        | CHARGE SOUND SYSTEM : Description .....   | 53        |
| Diagnosis Procedure .....   | 42        | <b>REMOVAL AND INSTALLATION .....</b>   | <b>54</b> |
| <b>POWER SWITCH SIGNAL CIRCUIT .....</b>  | <b>44</b> | <b>APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) CONTROL UNIT .....</b>               | <b>54</b> |
| Description .....   | 44        | Removal and Installation .....  | 54        |
| Component Function Check .....  | 44        | <b>START UP SOUND SPEAKER .....</b>   | <b>55</b> |
| Diagnosis Procedure .....   | 44        | Removal and Installation .....  | 55        |
| Component Inspection .....  | 45        | <b>APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SPEAKER .....</b>                    | <b>56</b> |
| <b>SYMPTOM DIAGNOSIS .....</b>  | <b>46</b> | Exploded View .....   | 56        |
| <b>APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SYSTEM SYMPTOMS .....</b>                          | <b>46</b> | Removal and Installation .....  | 56        |
| Symptom Table .....   | 46        | Disassembly and Assembly .....  | 56        |
| <b>THE APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) WARNING LAMP DOES NOT TURN ON OR OFF .....</b> | <b>47</b> | <b>APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) OFF SWITCH .....</b>                 | <b>57</b> |
| Description .....   | 47        | Exploded View .....   | 57        |
| Diagnosis Procedure .....   | 47        | Removal and Installation .....  |           |
| <b>THE DRIVING SOUND DOES NOT SOUND ...</b>   | <b>48</b> |   |           |
| Description .....   | 48        |   |           |
| Diagnosis Procedure .....   | 48        |   |           |

# PRECAUTIONS

< PRECAUTION >

## PRECAUTION

### PRECAUTIONS

#### Precaution for Technicians Using Medical Electric

INFOID:000000007631957

##### OPERATION PROHIBITION

###### **WARNING:**

- Parts with strong magnet is used in this vehicle.
- Technicians using a medical electric device such as pacemaker must never perform operation on the vehicle, as magnetic field can affect the device function by approaching to such parts.

##### NORMAL CHARGE PRECAUTION

###### **WARNING:**

- If a technician uses a medical electric device such as an implantable cardiac pacemaker or an implantable cardioverter defibrillator, the possible effects on the devices must be checked with the device manufacturer before starting the charge operation.
- As radiated electromagnetic wave generated by on board charger at normal charge operation may effect medical electric devices, a technician using a medical electric device such as implantable cardiac pacemaker or an implantable cardioverter defibrillator must not enter the vehicle compartment (including luggage room) during normal charge operation.

##### PRECAUTION AT TELEMATICS SYSTEM OPERATION

###### **WARNING:**

- If a technician uses implantable cardiac pacemaker or implantable cardioverter defibrillator (ICD), avoid the device implanted part from approaching within approximately 220 mm (8.66 in) from interior/exterior antenna.
- The electromagnetic wave of TCU might affect the function of the implantable cardiac pacemaker or the implantable cardioverter defibrillator (ICD), when using the service, etc.
- If a technician uses other medical electric devices than implantable cardiac pacemaker or implantable cardioverter defibrillator (ICD), the electromagnetic wave of TCU might affect the function of the device. The possible effects on the devices must be checked with the device manufacturer before TCU use.

##### PRECAUTION AT INTELLIGENT KEY SYSTEM OPERATION

###### **WARNING:**

- If a technician uses implantable cardiac pacemaker or implantable cardioverter defibrillator (ICD), avoid the device implanted part from approaching within approximately 220 mm (8.66 in) from interior/exterior antenna.
- The electromagnetic wave of Intelligent Key might affect the function of the implantable cardiac pacemaker or the implantable cardioverter defibrillator (ICD), at door operation, at each request switch operation, or at engine starting.
- If a technician uses other medical electric devices than implantable cardiac pacemaker or implantable cardioverter defibrillator (ICD), the electromagnetic wave of Intelligent Key might affect the function of the device. The possible effects on the devices must be checked with the device manufacturer before Intelligent Key use.

#### Point to Be Checked Before Starting Maintenance Work

INFOID:000000007631958

The high voltage system may starts automatically. It is required to check that the timer air conditioner and timer charge (during EVSE connection) are not set before starting maintenance work.

###### **NOTE:**

If the timer air conditioner or timer charge (during EVSE connection) is set, the high voltage system starts automatically even when the power switch is in OFF state.

#### Precaution for Supplemental Restraint System (SRS) "AIR BAG" and "SEAT BELT PRE-TENSIONER"

INFOID:000000007631959

The Supplemental Restraint System such as "AIR BAG" and "SEAT BELT PRE-TENSIONER", used along with a front seat belt, helps to reduce the risk or severity of injury to the driver and front passenger for certain types of collision. This system includes seat belt switch inputs and dual stage front air bag modules. The SRS

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
M  
N  
O  
P

VSP

# PRECAUTIONS

## < PRECAUTION >

system uses the seat belt switches to determine the front air bag deployment, and may only deploy one front air bag, depending on the severity of a collision and whether the front occupants are belted or unbelted. Information necessary to service the system safely is included in the “SRS AIR BAG” and “SEAT BELT” of this Service Manual.

### **WARNING:**

Always observe the following items for preventing accidental activation.

- To avoid rendering the SRS inoperative, which could increase the risk of personal injury or death in the event of a collision that would result in air bag inflation, all maintenance must be performed by an authorized NISSAN/INFINITI dealer.
- Improper maintenance, including incorrect removal and installation of the SRS, can lead to personal injury caused by unintentional activation of the system. For removal of Spiral Cable and Air Bag Module, see “SRS AIR BAG”.
- Never use electrical test equipment on any circuit related to the SRS unless instructed to in this Service Manual. SRS wiring harnesses can be identified by yellow and/or orange harnesses or harness connectors.

## PRECAUTIONS WHEN USING POWER TOOLS (AIR OR ELECTRIC) AND HAMMERS

### **WARNING:**

Always observe the following items for preventing accidental activation.

- When working near the Air Bag Diagnosis Sensor Unit or other Air Bag System sensors with the power switch ON, never use air or electric power tools or strike near the sensor(s) with a hammer. Heavy vibration could activate the sensor(s) and deploy the air bag(s), possibly causing serious injury.
- When using air or electric power tools or hammers, always switch the power switch OFF, disconnect the 12V battery, and wait at least 3 minutes before performing any service.

## Precautions for Removing Battery Terminal


INFOID:000000007631960

- When removing the 12V battery terminal, turn OFF the power switch and wait at least 5 minutes.

### **NOTE:**

ECU may be active for several minutes after the power switch is turned OFF. If the battery terminal is removed before ECU stops, then a DTC detection error or ECU data corruption may occur.

- Always disconnect the battery terminal within 60 minutes after turning OFF the power switch. Even when the power switch is OFF, the 12V battery automatic charge control may automatically start after a lapse of 60 minutes from power switch OFF.
- Disconnect 12V battery terminal according to the following steps.



## WORK PROCEDURE

1. Check that EVSE is not connected.

### **NOTE:**

If EVSE is connected, the air conditioning system may be automatically activated by the timer A/C function.

2. Turn the power switch OFF → ON → OFF. Get out of the vehicle. Close all doors (including back door).
3. Check that the charge status indicator lamp does not blink and wait for 5 minutes or more.

### **NOTE:**

If the battery is removed within 5 minutes after the power switch is turned OFF, plural DTCs may be detected.

4. Remove 12V battery terminal within 60 minutes after turning the power switch OFF → ON → OFF.

### **CAUTION:**

- After all doors (including back door) are closed, if a door (including back door) is opened before battery terminals are disconnected, start over from Step 1.
- After turning the power switch OFF, if “Remote A/C” is activated by user operation, stop the air conditioner and start over from Step 1.

### **NOTE:**

Once the power switch is turned ON → OFF, the 12V battery automatic charge control does not start for approximately 1 hour.

# PRECAUTIONS

## < PRECAUTION >

---

- For vehicles with the 2-batteries, be sure to connect the main battery and the sub battery before turning ON the power switch.

A

**NOTE:**

If the power switch is turned ON with any one of the terminals of main battery and sub battery disconnected, then DTC may be detected.

- After installing the 12V battery, always check "Self Diagnosis Result" of all ECUs and erase DTC.

B

**NOTE:**

The removal of 12V battery may cause a DTC detection error.

C

D

E

F

G

H

I

J

K

VSP

M

N

O

P

# PREPARATION


< PREPARATION >

## PREPARATION

### PREPARATION

#### Commercial Service Tools

INFOID:000000007631961

| Tool name  | Description   |
|--|---|
| <p data-bbox="162 514 267 546">Power tool</p>  <p data-bbox="828 630 901 651">PBIC0191E</p> | <p data-bbox="1006 514 1193 546">Loosening screws</p> |

# COMPONENT PARTS


< SYSTEM DESCRIPTION >

## SYSTEM DESCRIPTION

### COMPONENT PARTS

#### Component Parts Location

INFOID:000000007631962



A. Left inside of front bumper

B. Instrument lower panel LH reverse side

C. Cluster lid C

D. Inside glove box cover assembly

JSMIA0829ZZ

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
M  
N  
O  
P

VSP

# COMPONENT PARTS


## < SYSTEM DESCRIPTION >

|    | Component  | Description   |
|----|--|---|
| 1. | Approaching vehicle sound for pedestrians (VSP) speaker      | Refer to <a href="#">VSP-8, "Approaching Vehicle Sound For Pedestrians (VSP) Speaker"</a> .   |
| 2. | Combination meter  | <ul style="list-style-type: none"> <li>Transmits the following signals to the VSP control unit via the communication line. <ul style="list-style-type: none"> <li>READY to drive indicator lamp signal</li> <li>Power switch signal</li> <li>Vehicle speed signal</li> <li>Sound set request signal</li> <li>Sound signal</li> <li>Shift position signal</li> <li>Reverse warning buzzer signal</li> </ul> </li> <li>Sets the sound type of the start up sound function.</li> </ul> |
| 3. | Stop lamp switch   | Outputs the stop lamp switch signal to the VSP control unit.  |
| 4. | Start up sound speaker                                       | Refer to <a href="#">VSP-8, "Start Up Sound Speaker"</a> .  |
| 5. | Power switch   | Outputs the power switch signal to the VSP control unit.  |
| 6. | Approaching vehicle sound for pedestrians (VSP) warning lamp | Refer to <a href="#">VSP-9, "Approaching Vehicle Sound For Pedestrians (VSP) Warning Lamp"</a> .  |
| 7. | Approaching vehicle sound for pedestrians (VSP) control unit | Refer to <a href="#">VSP-9, "Approaching Vehicle Sound For Pedestrians (VSP) Control Unit"</a> .  |
| 8. | VCM  | Outputs the charge pulse signal to the VSP control unit.<br>Refer to <a href="#">EVC-17, "Component Parts Location"</a> for detailed installation location.   |

### Approaching Vehicle Sound For Pedestrians (VSP) Speaker

INFOID:000000007631963


- The VSP speaker is located on the left inside of the front bumper.
- The VSP speaker outputs the approaching vehicle sound for pedestrians (VSP) and charge sound according to the VSP speaker signal from the VSP control unit.



### Start Up Sound Speaker

INFOID:000000007631964

- The start up sound speaker is located on the reverse side of instrument lower panel LH.
- The start up sound speaker outputs the start up sound according to the start up sound speaker signal from the VSP control unit.






# COMPONENT PARTS

## < SYSTEM DESCRIPTION >

### Approaching Vehicle Sound For Pedestrians (VSP) Control Unit

INFOID:000000007631965

- The VSP control unit is located inside the glove box cover assembly.
- The VSP control unit contains 2 power amplifiers for the VSP speaker and start up sound speaker.
- The VSP control unit controls the following systems according to the signals from the units and switches.
  - VSP system
  - Start up sound system
  - Charging sound system
- When the VSP control unit judges that VSP system and charge sound system operation is necessary, it outputs the VSP speaker signal to the VSP speaker.
- When the VSP control unit judges that operation of the start up sound system is necessary, it outputs the start up sound speaker signal to the start up sound speaker.




### Approaching Vehicle Sound For Pedestrians (VSP) Warning Lamp

INFOID:000000007631967

- The VSP warning lamp (1) is located on the cluster lid C.
- The VSP warning lamp can check the operating status of the VSP system.

| VSP system status | VSP OFF indicator |
|-------------------|-------------------|
| Error             | ON                |



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
M  
N  
O  
P

VSP

# SYSTEM


< SYSTEM DESCRIPTION >

## SYSTEM

### System Description

INFOID:000000007631968

### SYSTEM DIAGRAM



### SYSTEM DESCRIPTION


- The VSP control unit is connected to the parts listed below, and it controls each system according to the input signals.
  - Combination meter
  - VCM
  - VSP warning lamp
  - Power switch
  - Stop lamp switch
  - VSP speaker
  - Start up sound speaker
- The combination meter sends the following signals to the VSP control unit via communication line.
  - READY to drive indicator lamp signal
  - Power switch signal
  - Vehicle speed signal
  - Sound set request signal
  - Sound signal
  - Shift position signal
  - Reverse warning buzzer signal
- The VSP control unit sends the following signals to the combination meter via communication line.
  - Power switch signal
  - Sound set signal
  - Sound signal
- The VCM outputs the charge pulse signal to the VSP control unit.
- The VSP control unit controls the following systems according to the signals from the units and switches.
  - VSP system
  - Start up sound system
  - Charge sound system
- The VSP control unit has a diagnostic function. Diagnosis can be performed using CONSULT.

# SYSTEM

< SYSTEM DESCRIPTION >

## Circuit Diagram

INFOID:000000007631969



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K

VSP

M  
N  
O  
P

## Fail-Safe

INFOID:000000007631970

The VSP control unit performs fail-safe control when a communication error with the combination meter is detected.

| System                | Specifications   |
|-----------------------|--|
| Start up sound system | Function stops by communication disruption.<br><b>NOTE:</b><br>Operation sound of the power switch operates. |
| VSP system            | Function stops by communication disruption.  |

# SYSTEM

## < SYSTEM DESCRIPTION >


| System              | Specifications     |
|---------------------|--------------------|
| Charge sound system | Function operates. |
| VSP warning lamp    | Function operates. |

## START UP SOUND SYSTEM

### START UP SOUND SYSTEM : System Description

INFOID:000000007631971

### SYSTEM DIAGRAM



### SYSTEM DESCRIPTION

- The start up sound is a system that produces a sound that is linked with the power switch and with the READY to drive indicator lamp on the combination meter.
- The start up sound function consists of the following 2 types.
  - Power switch operation sound when the power switch is operated.
  - READY effect sound that is linked to the READY to drive indicator lamp of the combination meter.
- A selection of 4 types (including OFF) of sound for the start up sound function is provided.
- The start up sound function sound types can be set using the combination meter.

### POWER SWITCH OPERATION SOUND

The power switch operation sound is a function that operates when the power switch is pressed.

#### Operation Description

- The VSP control unit uses the power switch signal from the power switch to determine the power switch operation sound.
- When the VSP control unit inputs the power switch signal, the start up sound speaker signal is output to the start up sound speaker.

#### Operation Condition

When the following conditions are met, the power switch operation sound operates.

| Operation condition |         |
|---------------------|---------|
| Power switch        | Pressed |

#### NOTE:

The power switch operation sound may not be able to respond normally if the power switch is pressed quickly.

#### Cancel Condition

The power switch operation sound stops when one of the following conditions is met.

- The power switch operation sound operation time is expired
- The READY effect sound operation condition is met
- The VSP system operation condition is met

#### Signal Path

- The VSP control unit judges operation of the power switch operation sound function based on the signal shown below, and it operates the power switch operation sound.

| Signal name         | Signal path                     |
|---------------------|---------------------------------|
| Power switch signal | Power switch → VSP control unit |


# SYSTEM

## < SYSTEM DESCRIPTION >

- When the VSP control unit judges that the power switch operation sound is necessary, it outputs the signal shown below.

| Signal name                   | Signal path                               |
|-------------------------------|---|
| Start up sound speaker signal | VSP control unit → Start up sound speaker |

### Timing Chart



|    | Description   |
|----|---|
| 1. | The power switch operation sound operates when the power switch is pressed. |
| 2. | The power switch operation sound operation time is expired.                 |
| 3. | When VSP system operates, the power switch operation sound stops.           |

## READY EFFECT SOUND

The READY effect sound is a function that operates through a link with the READY to drive indicator lamp of the combination meter.

### Operation Description

- The combination meter sends the READY to drive indicator lamp signal to the VSP control unit via the communication line.
- The VSP control unit determines the READY effect sound using the READY to drive indicator lamp signal from the combination meter.
- When the VSP control unit receives the READY to drive indicator lamp signal, the start up sound speaker signal is output to the start up sound speaker.

### Operation Condition

When the following conditions are met, the READY effect sound operates.

| Operation condition           |          |
|-------------------------------|----------|
| READY to drive indicator lamp | OFF → ON |

### Cancel Condition

When one of the following conditions is met, the READY effect sound operation stops.

| Cancel condition                              |           |
|---|-----------|
| The READY effect sound operation time expires |           |
| READY to drive indicator lamp                 | OFF       |
| Power switch                                  | OFF       |
| VSP system                                    | Operating |

### Signal Path

# SYSTEM

## < SYSTEM DESCRIPTION >


- The VSP control unit judges operation of the READY effect sound function based on the signal shown below, and it operates the READY effect sound.

| Signal name                          | Signal path  |
|--------------------------------------|--|
| Power switch signal                  | Power switch $\longrightarrow$ VSP control unit                |
| READY to drive indicator lamp signal | Combination meter $\xrightarrow{\text{COMM}}$ VSP control unit |

- When the VSP control unit judges that the READY effect sound is necessary, it outputs the signal shown below.

| Signal name                   | Signal path   |
|-------------------------------|---|
| Start up sound speaker signal | VSP control unit $\longrightarrow$ Start up sound speaker |

### Timing Chart



|    | Description   |
|----|---|
| 1. | When the READY to drive indicator lamp turns ON, the READY effect sound operates.         |
| 2. | The READY effect sound operation time ends.   |
| 3. | When the power switch is OFF, the READY effect sound operation stops.                     |
| 4. | When the READY to drive indicator lamp turns OFF, the READY effect sound operation stops. |
| 5. | When the VSP system operates, the READY effect sound operation stops.                     |

## APPROACHING VEHICLE SOUND FOR PEDESTRIANS(VSP) SYSTEM

### APPROACHING VEHICLE SOUND FOR PEDESTRIANS(VSP) SYSTEM : System


# SYSTEM

< SYSTEM DESCRIPTION >

## Description

INFOID:000000007631972

## SYSTEM DIAGRAM



## SYSTEM DESCRIPTION

- The VSP system has the function of warning the driver of pedestrians approaching the vehicle, according to signals received from the combination meter and the stop lamp switch
- The VSP system consists of the following 3 types.
  - Driving start sound
  - Driving sound
  - Reverse sound
- The VSP system operating status can be checked from the VSP warning lamp.
- The VSP system begins operating when the power switch is turned from OFF to READY.
- The VSP warning lamp turns ON when a malfunction occurs in the VSP system.

## DRIVING START SOUND

The driving start sound operates when the selector lever is shifted to “D” position and the brake pedal is released (when READY to drive indicator lamp ON).

### Operation Description

- The combination meter sends the following signals to the VSP control unit via the communication line.
  - Shift position signal
  - Vehicle speed signal
  - READY to drive indicator lamp signal
- The VSP control unit judges the driving start sound based on the signals input from the combination meter and on the stop lamp switch signal input from the stop lamp switch.
- When the VSP control unit judges that the driving start sound is necessary, it outputs the VSP speaker signal to the VSP speaker.
- The system switches to the driving sound after the driving start sound time ends.

### Operation Condition

The driving start sound operates when all of the following conditions are met.

| Operation condition           |                |
|-------------------------------|----------------|
| Selector lever                | “D” position   |
| Vehicle speed                 | 0 km/h (0 MPH) |
| READY to drive indicator lamp | ON             |
| Brake pedal                   | Released       |

### Cancel Condition

The driving start sound operation stops when the following condition is met.

# SYSTEM

## < SYSTEM DESCRIPTION >

|                  |    |
|------------------|----|
| Cancel condition |    |
| Reverse sound    | ON |

### NOTE:

The system switches to the driving sound after the driving start sound time ends.

### Signal Path


- The VSP control unit judges operation of the driving start sound function based on the signal shown below, and it operates the driving start sound.

| Signal name                          | Signal path  |
|--------------------------------------|--|
| Shift position signal                | Combination meter $\xrightarrow{\text{COMM}}$ VSP control unit |
| Vehicle speed signal                 |  |
| READY to drive indicator lamp signal |  |
| Stop lamp switch signal              | Stop lamp switch $\longrightarrow$ VSP control unit            |

- When the VSP control unit judges that the driving start sound is necessary, it outputs the signal shown below.

| Signal name        | Signal path                                    |
|--------------------|--|
| VSP speaker signal | VSP control unit $\longrightarrow$ VSP speaker |

### Timing Chart



|    | Description  |
|----|--|
| 1. | The driving start sound operates when the selector lever is shifted to "D" position and the brake pedal is released. |
| 2. | If the selector lever is moved to "R" position, the driving sound stops.   |
| 3. | The system switches to the driving sound after the driving start sound time ends.                                    |

### DRIVING SOUND

- The driving sound is a function that operates according to the vehicle speed.
- The driving sound tone frequency changes in accordance with the vehicle speed.

### Operation Description

- The combination meter sends the following signals to the VSP control unit via the communication line.
  - Vehicle speed signal
  - READY to drive indicator lamp signal
- The VSP control unit judges the driving sound based on the signals input from the combination meter.



# SYSTEM

## < SYSTEM DESCRIPTION >

- When the VSP control unit judges that the driving sound is necessary, it outputs the VSP speaker signal to the VSP speaker.

### Operation Condition

The driving sound operates when the following conditions are met.

| Operation condition           |              |                          |
|-------------------------------|--------------|--------------------------|
| Vehicle speed                 | Accelerating | 1 km/h (0.6 MPH) or more |
|                               | Decelerating | 25 km/h (16 MPH) or less |
| READY to drive indicator lamp |              | ON                       |
| Selector lever                |              | "D" position             |

### Cancel Condition

The driving sound operation stops when the following conditions are met.

| Cancel condition              |              |                            |
|-------------------------------|--------------|----------------------------|
| Vehicle speed                 | Accelerating | 30 km/h (19 MPH) or more   |
|                               | Decelerating | Less than 1 km/h (0.6 MPH) |
| READY to drive indicator lamp |              | OFF                        |

### Signal Path


- The VSP control unit judges operation of the driving sound function based on the signals shown below, and it operates the driving sound.

| Signal name                          | Signal path                                      |
|--------------------------------------|--|
| Vehicle speed signal                 | Combination meter <b>COMM</b> → VSP control unit |
| READY to drive indicator lamp signal |  |

- When the VSP control unit judges that the driving sound is necessary, it outputs the signal shown below.

| Signal name        | Signal path                    |
|--------------------|--------------------------------|
| VSP speaker signal | VSP control unit → VSP speaker |

### Timing Chart



JSMIA0470GB

# SYSTEM

## < SYSTEM DESCRIPTION >

| Operation contents |   |
|--------------------|---|
| 1.                 | The driving sound operates up to approximately 30 km/h (19 MPH) while accelerating.                           |
| 2.                 | The driving sound stops when approximately 30 km/h (19 MPH) is reached.                                       |
| 3.                 | The driving sound operates when the speed falls to approximately 25 km/h (16 MPH) or less while decelerating. |
| 4.                 | The driving sound stops while the vehicle stops (fades out and stops).  |

### REVERSE SOUND

The reverse sound operates when the selector lever is shifted to “R” position.

#### Operation Description

- The combination meter sends the following signals to the VSP control unit via the communication line.
  - Shift position signal
  - Reverse warning buzzer signal
  - READY to drive indicator lamp signal
- The VSP control unit judges the reverse sound based on the signals input from the combination meter.
- When the VSP control unit judges that the reverse sound is necessary, it outputs the VSP speaker signal to the VSP speaker.

#### Operation Condition

The reverse sound operates when the following conditions are met.

| Operation condition           |              |
|-------------------------------|--------------|
| Selector lever                | “R” position |
| READY to drive indicator lamp | ON           |


#### Cancel Condition

The reverse sound operation stops when the following condition is met.


| Operation condition |                         |
|---------------------|-------------------------|
| Selector lever      | Other than “R” position |

#### Signal Path

- The VSP control unit judges operation of the reverse sound based on the signals shown below, and operates the driving sound.

| Signal name                   | Signal path  |
|-------------------------------|--|
| Shift position signal         | Combination meter  VSP control unit |
| Reverse warning buzzer signal |  |


- When the VSP control unit judges that the reverse sound is necessary, it outputs the signal shown below.

| Signal name        | Signal path  |
|--------------------|--|
| VSP speaker signal | VSP control unit  VSP speaker |

# SYSTEM

## < SYSTEM DESCRIPTION >

### Timing Chart



### Operation contents

1. The reverse sound operates when the selector lever is shifted to "R" position.
2. The reverse sound stops when the selector lever is shifted to other than "R" position.

### VSP SYSTEM MALFUNCTION DETECTION FUNCTION

When a malfunction in the VSP system is detected, the VSP warning lamp turns ON.

#### Signal Path

- When the VSP control unit detects a VSP system malfunction, it outputs the VSP warning lamp signal to the VSP warning lamp.
- The VSP control unit turns the VSP warning lamp ON/OFF when the signal shown below is input.

| Signal name             | Signal path                         |
|-------------------------|-------------------------------------|
| VSP warning lamp signal | VSP control unit → VSP warning lamp |


## CHARGE SOUND SYSTEM

### CHARGE SOUND SYSTEM : System Description

INFOID:000000007631973

VSP

### SYSTEM DIAGRAM



### SYSTEM DESCRIPTION

- The charge sound system is a function that notifies of the charge connector status and the charge acceptance status.
- The charge sound system operates when the power switch is OFF.
- The charge sound system consists of the following 2 types and operates through a link with the charging status indicator.
  - Plug-in detection sound.
  - Charge acceptance sound.

# SYSTEM

## < SYSTEM DESCRIPTION >

### PLUG-IN DETECTION SOUND

- The plug-in detection sound notifies that the charge connector is engaged normally.
- During quick charge, the plug-in detection sound does not operate.

#### Operation Description

- The VCM outputs the charge pulse signal to the VSP control unit.
- The VSP control unit determines the plug-in detection sound using the charge pulse signal (2 pulses) from the VCM.
- When the VSP control unit inputs the charge pulse signal (2 pulses), the VSP speaker signal is outputs to the VSP speaker.

#### Operation Condition

The plug-in detection sound operates when all of the following conditions are met.

| Operation condition |                   |
|---------------------|-------------------|
| Power switch        | OFF               |
| Charge connector    | Normal connection |

### CHARGE ACCEPTANCE SOUND

The charge acceptance sound notifies that the charge is accepted.

#### Operation Description

- The VCM outputs the charge pulse signal to the VSP control unit.
- The VSP control unit determines the charge acceptance sound using the charge pulse signal (3 pulses) from the VCM.
- When the VSP control unit inputs the charge pulse signal (3 pulses), the VSP speaker signal is output to the VSP speaker.

#### Operation Condition

The charge acceptance sound operates when all of the following conditions are met.

| Operation condition |                         |
|---------------------|-------------------------|
| Power switch        | OFF                     |
| Charge              | When charge is accepted |

#### Signal Path

- The VSP control unit uses the signal shown below to judge the plug-in detection sound function and charge acceptance sound function, and it activates the plug-in detection sound and charge acceptance sound.

| Signal name         | Signal path            |
|---------------------|------------------------|
| Charge pulse signal | VCM → VSP control unit |


- When the VSP control unit judges that the plug-in detection sound and charge acceptance sound are necessary, it outputs the signal shown below.

| Signal name        | Signal path                    |
|--------------------|--------------------------------|
| VSP speaker signal | VSP control unit → VSP speaker |

# SYSTEM

< SYSTEM DESCRIPTION >

## TIMING CHART



| Description |  |
|-------------|--|
| 1.          | When the charge connector engaged normally, the plug-in detection sound operates (when the charge pulse signal (2 pulses) is input). |
| 2.          | When charging is accepted, the charge acceptance sound operates (when the charge pulse signal (3 pulses) is input).                  |

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
M  
N  
O  
P

VSP

# DIAGNOSIS SYSTEM (VSP)

< SYSTEM DESCRIPTION >

## DIAGNOSIS SYSTEM (VSP)

### CONSULT Function

INFOID:000000007631974

### APPLICATION ITEM

CONSULT can display each diagnostic item using the diagnostic test modes shown as per the following:

| Test mode               | Function  |
|-------------------------|---|
| Self Diagnostic Results | Approaching vehicle sound for pedestrian control unit checks the conditions and displays memorized error. |
| Data Monitor            | Approaching vehicle sound for pedestrian control unit input/output data in real time.                     |
| Active Test             | Gives a drive signal to a load to check the operation.  |

### SELF-DIAGNOSTIC RESULTS

For details, refer to [VSP-27. "DTC Index"](#).

### DATA MONITOR

| Monitor item     | Display     | Description   |
|------------------|-------------|---|
| IGNITION SW      | On          | Power switch status input from the power switch supply.   |
|                  | Off         |   |
| BRAKE SW         | On          | Stop lamp switch status input from the stop lamp switch.  |
|                  | Off         |   |
| VSP OFF SW       | Off         | This item is displayed, but cannot be monitored.  |
| PUSH SW          | On          | Power switch status input from the power switch.  |
|                  | Off         |   |
| VCM INPUT SIG    | Hi          | Charge connector status input from the VCM.   |
|                  | Lo          |   |
| READY OP IND SIG | On          | READY to drive indicator lamp status input from the combination meter via the communication line.   |
|                  | Off         |   |
| IGN STATS SIG    | On          | Power switch status input from the combination meter via the communication line.  |
|                  | Off         |   |
| VEHICLE SPEED    | 0 - 63 km/h | Vehicle speed signal value input from the combination meter via the communication line.<br><b>NOTE:</b><br>63 km/h (39.1 MPH) or faster is fixed at 63 km/h (39.1 MPH). |
| ENG STATUS SIG   | Off         | This item is displayed, but cannot be monitored.  |
| SOUND SET REQ    | On          | Start up sound setting requirement status display input from the combination meter via the communication line.  |
|                  | Off         |   |
| SOUND            | 1           | Start up sound setting display input from the combination meter via the communication line.   |
|                  | 2           |   |
|                  | 3           |   |
|                  | 4           |   |
| SHIFT POS SIG    | P or N      | The shift position status input from the combination meter via the communication line.  |
|                  | R           |   |
|                  | D or B      |   |
| REVERSE BUZZER   | On          | Reverse warning buzzer status input from the combination meter via the communication line.  |
|                  | Off         |   |

### ACTIVE TEST

# DIAGNOSIS SYSTEM (VSP)

## < SYSTEM DESCRIPTION >

| Active test item       | Function   |        |
|------------------------|--|--------|
| VSP SPEAKER            | The VSP speaker operation can be checked.<br><b>NOTE:</b><br>Activates the reverse sound at a higher sound level than normal operation.            | A<br>B |
| START UP SOUND SPEAKER | The start up sound speaker operation can be checked.<br><b>NOTE:</b><br>Activates the reverse sound at a higher sound level than normal operation. | C      |
| VSP IND                | The VSP warning lamp operation can be checked.<br><b>NOTE:</b><br>The VSP warning lamp flashes (1 Hz).   | D      |

E

F

G

H

I

J

K

VSP

M

N

O

P

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) CONTROL UNIT

< ECU DIAGNOSIS INFORMATION >

## ECU DIAGNOSIS INFORMATION

### APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) CONTROL UNIT

Reference Value

INFOID:000000007631975

VALUES ON THE DIAGNOSIS TOOL

CONSULT MONITOR ITEM


| Monitor item          | Condition       |  | Value/Status   |
|-----------------------|-----------------|--|--|
| IGNITION SW           | Power switch ON | Power switch READY position                                      | On   |
|                       |                 | Power switch other than READY position                           | Off  |
| BRAKE SW              | Power switch ON | When brake pedal is depressed (stop lamp switch OFF)             | On   |
|                       |                 | When brake pedal is not depressed (stop lamp switch ON)          | Off  |
| VSP OFF SW            | Power switch ON | <b>NOTE:</b><br>This item is displayed, but cannot be monitored. | Off  |
| PUSH SW               | Power switch ON | When power switch is pressed                                     | On   |
|                       |                 | When power switch is not pressed                                 | Off  |
| VCM INPUT SIG         | Power switch ON | Charge connector connected                                       | Hi   |
|                       |                 | Charge connector not connected                                   | Low  |
| READY OP IND SIG      | Power switch ON | READY to drive indicator lamp ON                                 | On   |
|                       |                 | READY to drive indicator lamp OFF                                | Off  |
| IGN STATUS SIG        | Power switch ON | Power switch READY position                                      | On   |
|                       |                 | Power switch other than READY position                           | Off  |
| VEHICLE SPEED         | Power switch ON | While driving  | Approximately equal to speedometer reading<br><b>NOTE:</b><br>Indicates 63 km/h (39.1 MPH) when speed is 63 km/h (39.1 MPH) or higher. |
| ENG STATUS SIG        | Power switch ON | <b>NOTE:</b><br>This item is displayed, but cannot be monitored. | Off  |
| SOUND SET REQ         | Power switch ON | Start up sound type was set.                                     | On   |
|                       |                 | Other than the above   | Off  |
| SOUND                 | Power switch ON | Start up sound setting is "1".                                   | 1  |
|                       |                 | Start up sound setting is "2".                                   | 2  |
|                       |                 | Start up sound setting is "3".                                   | 3  |
|                       |                 | Start up sound setting is "OFF".                                 | 4  |
| SHIFT POSITION SIGNAL | Power switch ON | Selector lever is in "P" or "N" position.                        | P or N   |
|                       |                 | Selector lever is in "R" position.                               | R  |
|                       |                 | Selector lever is in "D" position.                               | D or B   |
| REVERSE BUZZER        | Power switch ON | Reverse warning buzzer operating                                 | On   |
|                       |                 | Reverse warning buzzer not operating                             | Off  |



# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) CONTROL UNIT

< ECU DIAGNOSIS INFORMATION >

## TERMINAL LAYOUT



## PHYSICAL VALUES





| Terminal No.<br>(Wire color) |        | Description                           |                  | Condition                        | Value<br>(Approx.)   |
|------------------------------|--------|---------------------------------------|------------------|----------------------------------|--|
| +                            | -      | Signal name                           | Input/<br>Output |                                  |  |
| 1<br>(B)                     | Ground | Ground                                | —                | Power switch ON                  | 0 V  |
| 2<br>(L)                     | Ground | Communication signal<br>(METER → VSP) | Input            | Power switch ON                  | <p><b>NOTE:</b><br/>Waveform shows reference values.</p> <p>0 - 12 V</p> |
| 3<br>(SB)                    | Ground | Power switch signal                   | Input            | Power switch ON                  | 0 V  |
|                              |        |                                       |                  | When power switch is not pressed | 12 V   |
| 4<br>(P)                     | Ground | Communication signal<br>(VSP → METER) | Output           | Power switch ON                  | <p><b>NOTE:</b><br/>Waveform shows reference values.</p> <p>0 - 12 V</p> |

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
M  
N  
O  
P

VSP

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) CONTROL UNIT

## < ECU DIAGNOSIS INFORMATION >

| Terminal No.<br>(Wire color) |           | Description                   |                  | Condition  | Value<br>(Approx.)   |                 |
|------------------------------|-----------|-------------------------------|------------------|--|--|-----------------|
| +                            | -         | Signal name                   | Input/<br>Output |  |  |                 |
| 6<br>(Y)                     | Ground    | Charge pulse signal           | Input            | Power switch ON  |  <p>When charge connector is connected</p>                                    |                 |
|                              |           |                               |                  | <ul style="list-style-type: none"> <li>Power switch is OFF</li> <li>Charge is accepted.</li> </ul>  |  |                 |
|                              |           |                               |                  | Other than the above   | 0 V  |                 |
| 8<br>(Y)                     | 7<br>(L)  | VSP speaker signal            | Output           | Power switch ON  | <p><b>NOTE:</b><br/>Waveform varies depending on tone and sound level.</p>   |                 |
| 10<br>(GR)                   | —         | K- LINE (CONSULT)             | —                | —  | —  |                 |
| 11<br>(GR)                   | Ground    | Power switch supply           | Input            | Power switch ON  | —  | Battery voltage |
| 12<br>(SB)                   | Ground    | Stop lamp switch signal       | Input            | Power switch ON  | When brake pedal is not depressed  | 0 V             |
|                              |           |                               |                  | Power switch OFF   | When the brake pedal is depressed  | 12 V            |
| 13<br>(L)                    | Ground    | Battery power supply          | Input            | Power switch OFF   | —  | Battery voltage |
| 14<br>(LG)                   | Ground    | VSP warning lamp signal       | Output           | Power switch ON  | VSP warning lamp is ON.  | 0 V             |
|                              |           |                               |                  | Power switch OFF   | VSP warning lamp is OFF.   | 12 V            |
| 16<br>(W)                    | 15<br>(R) | Start up sound speaker signal | Output           | Power switch ON  | <p><b>NOTE:</b><br/>Waveform varies depending on tone and sound level.</p>  |                 |

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) CONTROL UNIT

< ECU DIAGNOSIS INFORMATION >

## Fail-Safe

INFOID:000000007631976

The VSP control unit performs fail-safe control when a communication error with the combination meter is detected.

| System                | Specifications   |
|-----------------------|--|
| Start up sound system | Function stops by communication disruption.<br><b>NOTE:</b><br>Operation sound of the power switch operates. |
| VSP system            | Function stops by communication disruption.  |
| Charge sound system   | Function operates.   |

## DTC Index

INFOID:000000007631977

| Display item<br>[Code]  | Malfunction is detected when...  | Reference              |
|-------------------------|--|------------------------|
| COMM CIRCUIT<br>[U1431] | Communications signal from combination meter could not be received continuously for 2 seconds or more (when power switch ON or READY). | <a href="#">VSP-31</a> |

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
M  
N  
O  
P

VSP

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SYSTEM


< WIRING DIAGRAM >

## WIRING DIAGRAM


### APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SYSTEM

#### Wiring Diagram

INFOID:000000007631978

For connector terminal arrangements, harness layouts, and alphabets in a  (option abbreviation; if not described in wiring diagram), refer to [GI-12. "Connector Information"](#).

#### APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SYSTEM



2011/07/29

JRLWC1111GB

# DIAGNOSIS AND REPAIR WORKFLOW

< BASIC INSPECTION >


## BASIC INSPECTION

### DIAGNOSIS AND REPAIR WORKFLOW

Work Flow

INFOID:000000007631979

#### OVERALL SEQUENCE



Reference 1...[VSP-27, "DTC Index"](#).

#### DETAILED FLOW

##### 1.OBTAIN INFORMATION ABOUT SYMPTOM

Interview the customer to obtain as much information as possible about the conditions and environment under which the malfunction occurred.

>> GO TO 2.

##### 2.CHECK SYMPTOM

- Check the symptom based on the information obtained from the customer.
- Check if any other malfunctions are present.

>> GO TO 3.

##### 3.CHECK CONSULT SELF-DIAGNOSIS RESULTS

1. Connect CONSULT and perform self-diagnosis. Refer to [VSP-27, "DTC Index"](#).
2. When DTC is detected, follow the instructions below:
  - Record DTC and Freeze Frame Data.

Are self-diagnosis results normal?

YES >> GO TO 5.

## DIAGNOSIS AND REPAIR WORKFLOW

< BASIC INSPECTION >

---

NO >> GO TO 4.

### 4.NARROW DOWN MALFUNCTIONING PARTS BY SYMPTOM DIAGNOSIS

---

Perform symptom diagnosis and narrow down the malfunctioning parts.

>> GO TO 5.

### 5.REPAIR OR REPLACE MALFUNCTIONING PARTS

---

Repair or replace malfunctioning parts.

**NOTE:**

If DTC is displayed, erase DTC after repairing or replacing malfunctioning parts.

>> GO TO 6.

### 6.FINAL CHECK

---

Check that the VSP system operates normally.

Does it operate normally?

YES >> INSPECTION END

NO >> GO TO 1.

# U1431 COMM CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

## DTC/CIRCUIT DIAGNOSIS

### U1431 COMM CIRCUIT

#### Description

INFOID:000000007631980

The communications line (METER → VSP) sends signals needed for VSP system control from the combination meter.

#### DTC Logic

INFOID:000000007631981

#### DTC DETECTION LOGIC

| DTC   | Display contents of CONSULT | Diagnostic item is detected when...   | Probable malfunction location    |
|-------|-----------------------------|---|----------------------------------|
| U1431 | COMM CIRCUIT                | Communications signal from combination meter could not be received continuously for 2 seconds or more (power switch ON or READY). | Communication line (METER → VSP) |

#### Diagnosis Procedure

INFOID:000000007631982

#### 1. CHECK COMMUNICATION LINE (METER → VSP) SIGNAL CIRCUIT

1. Power switch OFF
2. Disconnect VSP control unit and combination meter connector.
3. Check continuity between VSP control unit harness connector and combination meter harness connector.

| VSP control unit |          | Combination meter |          | Continuity |
|------------------|----------|-------------------|----------|------------|
| Connector        | Terminal | Connector         | Terminal |            |
| M47              | 2        | M34               | 10       | Existed    |

4. Check continuity between VSP control unit harness connector and ground.

| VSP control unit |          | Ground | Continuity  |
|------------------|----------|--------|-------------|
| Connector        | Terminal |        |             |
| M47              | 2        |        | Not existed |

Is the inspection result normal?

- YES >> GO TO 2.  
 NO >> Repair harness or connector.

#### 2. CHECK COMMUNICATION LINE (METER → VSP) INPUT SIGNAL

1. Connect VSP control unit and combination meter connector.
2. Power switch ON.
3. Check voltage between VSP control unit harness connector and ground.


| Terminal         |          | Voltage<br>(Approx.) |
|------------------|----------|----------------------|
| (+)              |          |                      |
| VSP control unit | (-)      |                      |
| Connector        | Terminal |                      |

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
M  
N  
O  
P

VSP

# U1431 COMM CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

|     |   |        |   |
|-----|---|--------|---|
| M47 | 2 | Ground | <p><b>NOTE:</b><br/>Waveform shows reference values.</p>  <p>JSMIA0536GB<br/>0 - 12 V</p> |
|-----|---|--------|---|

Is the inspection result normal?

YES >> INSPECTION END

NO >> Replace combination meter. Refer to [MWI-96. "Removal and Installation"](#).



# POWER SUPPLY AND GROUND CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

## POWER SUPPLY AND GROUND CIRCUIT

APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) CONTROL UNIT

APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) CONTROL UNIT :

### Diagnosis Procedure

INFOID:000000007631983

#### 1. CHECK FUSE

Check for blown fuses.

| Power source         | Fuse No. |
|----------------------|----------|
| Battery power supply | 11       |
| Power switch ON      | 5        |

Is the inspection result normal?

YES >> GO TO 2.

NO >> Be sure to eliminate cause of malfunction before installing new fuse.

#### 2. CHECK POWER SUPPLY CIRCUIT

1. Power switch ON.
2. Check voltage between VSP control unit harness connector and ground.

| Signal name            | Connector No. | Terminal No. | Power switch position | Value (Approx.) |
|------------------------|---------------|--------------|-----------------------|-----------------|
| Battery power supply   | M47           | 13           | OFF                   | Battery voltage |
| Power switch ON signal |               | 11           | ON                    | Battery voltage |

Is the inspection result normal?

YES >> GO TO 3.

NO >> Repair or replace VSP control unit power supply harness.

#### 3. CHECK GROUND CIRCUIT

1. Power switch OFF.
2. Disconnect VSP control unit connector.
3. Check continuity between VSP control unit harness connector and ground.

| VSP control unit |          | Ground | Continuity |
|------------------|----------|--------|------------|
| Connector        | Terminal |        |            |
| M47              | 1        |        | Existed    |

Is the inspection result normal?

YES >> INSPECTION END

NO >> Repair or replace VSP control unit ground harness.

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
M  
N  
O  
P

VSP

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SPEAKER SIGNAL CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

## APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SPEAKER SIGNAL CIRCUIT

### Description

INFOID:000000007631984

The VSP control unit outputs the VSP speaker signal to the VSP speaker.

### Component Function Check

INFOID:000000007631985

#### 1. CHECK VSP SPEAKER OPERATION

1. Connect the CONSULT.
2. Select the "ACTIVE TEST" for the "VSP" and perform the "VSP SPEAKER".

>> INSPECTION END

### Diagnosis Procedure

INFOID:000000007631986

#### 1. CHECK VSP SPEAKER SIGNAL CIRCUIT

1. Power switch OFF.
2. Disconnect VSP control unit and VSP speaker connector.
3. Check continuity between VSP control unit harness connector and VSP speaker harness connector.

| VSP control unit |          | VSP speaker |          | Continuity |
|------------------|----------|-------------|----------|------------|
| Connector        | Terminal | Connector   | Terminal |            |
| M47              | 7        | E42         | 2        | Existed    |
|                  | 8        |             | 1        |            |

4. Check continuity between VSP control unit harness connector and ground.

| VSP control unit |          | Ground | Continuity  |
|------------------|----------|--------|-------------|
| Connector        | Terminal |        |             |
| M47              | 7        |        | Not existed |
|                  | 8        |        |             |

Is the inspection result normal?

YES >> GO TO 2.


NO >> Repair harness or connector.

#### 2. CHECK VSP SPEAKER OUTPUT SIGNAL

1. Connect VSP control unit and VSP speaker connector.
2. Power switch ON.
3. Check signal between VSP control unit harness connector.

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SPEAKER SIGNAL CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

| Terminals        |          |           |          | Voltage<br>(Approx.)  |
|------------------|----------|-----------|----------|---|
| (+)              |          | (-)       |          |   |
| VSP control unit |          |           |          |   |
| Connector        | Terminal | Connector | Terminal |   |
| M47              | 8        | M47       | 7        | <p><b>NOTE:</b><br/>Waveform varies depending on tone and sound level.</p> <div style="text-align: center;">  </div> <p style="text-align: right; font-size: small;">JSMIA0539GB</p> |

**Is the inspection result normal?**

YES >> INSPECTION END

NO >> Replace VSP control unit. Refer to [VSP-56. "Removal and Installation"](#).

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
M  
N  
O  
P

VSP

# START UP SOUND SPEAKER SIGNAL CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

## START UP SOUND SPEAKER SIGNAL CIRCUIT

### Description

INFOID:000000007631987

The VSP control unit outputs the start up sound speaker signal to the start up sound speaker.

### Component Function Check

INFOID:000000007631988

#### 1. CHECK START UP SOUND SPEAKER OPERATION

1. Connect the CONSULT.
2. Select the "ACTIVE TEST" for the "VSP" and perform the "START UP SOUND SPEAKER".

>> INSPECTION END

### Diagnosis Procedure

INFOID:000000007631989

#### 1. CHECK START UP SOUND SPEAKER SIGNAL CIRCUIT

1. Power switch OFF.
2. Disconnect VSP control unit and start up sound speaker connector.
3. Check continuity between VSP control unit harness connector and start up sound speaker harness connector.

| VSP control unit |          | Start up sound speaker |          | Continuity |
|------------------|----------|------------------------|----------|------------|
| Connector        | Terminal | Connector              | Terminal |            |
| M47              | 15       | M48                    | 2        | Existed    |
|                  | 16       |                        | 1        |            |

4. Check continuity between VSP control unit harness connector and ground.

| VSP control unit |          | Ground | Continuity  |
|------------------|----------|--------|-------------|
| Connector        | Terminal |        |             |
| M47              | 15       |        | Not existed |
|                  | 16       |        |             |

Is the inspection result normal?

YES >> GO TO 2.


NO >> Repair harness or connector.

#### 2. CHECK START UP SOUND SPEAKER OUTPUT SIGNAL

1. Connect VSP control unit and start up sound speaker connector.
2. Power switch ON.
3. Check signal between VSP control unit harness connector.

# START UP SOUND SPEAKER SIGNAL CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

| Terminals        |          |              |          | Voltage<br>(Approx.)  |
|------------------|----------|--------------|----------|---|
| (+) Terminal     |          | (-) Terminal |          |   |
| VSP control unit |          |              |          |   |
| Connector        | Terminal | Connector    | Terminal |   |
| M47              | 16       | M47          | 15       | <p><b>NOTE:</b><br/>Waveform varies depending on tone and sound level.</p>  <p style="text-align: right;"><small>JSMIA0564GB</small></p> |

Is the inspection result normal?

YES >> INSPECTION END

NO >> Replace VSP control unit. Refer to [VSP-56. "Removal and Installation"](#).

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
M  
N  
O  
P

VSP

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) WARNING LAMP SIGNAL CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

## APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) WARNING LAMP SIGNAL CIRCUIT

### Description

INFOID:000000007631994

VSP warning lamp turns ON/OFF according to VSP warning lamp signal transmitted from VSP control unit.

### Component Function Check

INFOID:000000007627199

### 1.CHECK VSP WARNING LAMP OPERATION

1. Connect the CONSULT.
2. Select the "ACTIVE TEST" for the "VSP" and perform the "VSP IND".

|             |                    |
|-------------|--------------------|
| ACTIVE TEST | VSP warning lamp   |
| ON          | : Turns ON         |
| OFF         | : Does not turn ON |

>> INSPECTION END

### Diagnosis Procedure

INFOID:000000007631995

### 1.CHECK FUSE

Check that the following fuse is not fusing.

| Location         | Fuse No. | Capacity |
|------------------|----------|----------|
| Fuse block (J/B) | 1        | 10 A     |

Is the fuse fusing?

- YES >> Replace the fuse after repairing the applicable circuit.  
NO >> GO TO 2.

### 2.CHECK VSP WARNING LAMP POWER SUPPLY CIRCUIT

1. Power switch OFF.
2. Disconnect front passenger air bag OFF indicator harness connector.
3. Power switch ON.
4. Check voltage between front passenger air bag OFF indicator harness connector and ground.

| Terminals                             |          | Voltage (Approx.) |
|---------------------------------------|----------|-------------------|
| (+)                                   | (-)      |                   |
| Front passenger air bag OFF indicator |          | 12 V              |
| Connector                             | Terminal |                   |
| M63                                   | 3        |                   |
|                                       | Ground   |                   |

Is the inspection result normal?

- YES >> GO TO 3.  
NO >> Repair the harness or connector.

### 3.CHECK VSP WARNING LAMP SIGNAL CIRCUIT

1. Power switch OFF.
2. Disconnect VSP control unit harness connector.
3. Check the continuity between VSP control unit harness connector and front passenger air bag OFF indicator harness connector.

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) WARNING LAMP SIGNAL CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

| VSP control unit |          | Front passenger air bag OFF indicator |          | Continuity |
|------------------|----------|---------------------------------------|----------|------------|
| Connector        | Terminal | Connector                             | Terminal |            |
| M47              | 14       | M63                                   | 4        | Existed    |

4. Check the continuity between VSP control unit harness connector and ground.

| VSP control unit |          | Ground | Continuity  |
|------------------|----------|--------|-------------|
| Connector        | Terminal |        |             |
| M47              | 14       |        | Not existed |

Is the inspection result normal?

YES >> INSPECTION END.

NO >> Repair the harness or connector.

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
M  
N  
O  
P

VSP

# STOP LAMP SWITCH SIGNAL CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

## STOP LAMP SWITCH SIGNAL CIRCUIT

### Description

INFOID:000000007631996

The Stop lamp switch outputs the stop lamp switch signal to the VSP control unit.

### Component Function Check

INFOID:000000007631997

#### 1. CHECK STOP LAMP SWITCH INPUT SIGNAL

1. Connect the CONSULT.
2. Select the "DATA MONITOR" for the "VSP" and check the "BRAKE SW" monitor value.

|                                   | "BRAKE SW" |
|-----------------------------------|------------|
| When brake pedal is not depressed | : Off      |
| When brake pedal is depressed     | : On       |

>> INSPECTION END

### Diagnosis Procedure

INFOID:000000007631998

#### 1. STOP LAMP SWITCH POWER SUPPLY CIRCUIT

1. Power switch OFF.
2. Disconnect stop lamp switch connector.
3. Power switch ON.
4. Check voltage between stop lamp switch harness connector and ground.

| Terminal     |        | Voltage<br>(Approx.) |
|--------------|--------|----------------------|
| (+)          | (-)    |                      |
| Stop lamp SW | Ground | 12 V                 |
| Connector    |        |                      |
| E102         | 1      |                      |

Is the inspection result normal?

- YES >> GO TO 2.  
NO >> Check harness between fuse and stop lamp switch.

#### 2. CHECK STOP LAMP SWITCH SIGNAL CIRCUIT

1. Power switch OFF.
2. Disconnect VSP control unit connector.
3. Check continuity between VSP control unit harness connector and stop lamp switch harness connector.

| VSP control unit |          | Stop lamp SW |          | Continuity |
|------------------|----------|--------------|----------|------------|
| Connector        | Terminal | Connector    | Terminal |            |
| M47              | 12       | E102         | 2        | Existed    |

4. Check continuity between VSP control unit harness connector and ground.

| VSP control unit |          | Ground | Continuity  |
|------------------|----------|--------|-------------|
| Connector        | Terminal |        |             |
| M47              | 12       |        | Not existed |

Is the inspection result normal?

- YES >> GO TO 3.  
NO >> Repair the harnesses or connector.

#### 3. CHECK STOP LAMP SWITCH INPUT SIGNAL



# STOP LAMP SWITCH SIGNAL CIRCUIT

## < DTC/CIRCUIT DIAGNOSIS >

1. Connect VSP control unit and stop lamp switch connector.
2. Power switch ON.
3. Check voltage between VSP control unit harness connector and ground.

| Terminals        |          | Condition                         | Voltage (Approx.) |
|------------------|----------|-----------------------------------|-------------------|
| (+)              | (-)      |                                   |                   |
| VSP control unit |          | When brake pedal is depressed     | 12 V              |
| Connector        | Terminal |                                   |                   |
| M47              | 12       | When brake pedal is not depressed | 0 V               |

Is the inspection result normal?

- YES >> Replace the VSP control unit. Refer to [VSP-54, "Removal and Installation"](#).  
 NO >> Refer to [VSP-41, "Component Inspection"](#).

## Component Inspection

INFOID:000000007631999

### 1. CHECK STOP LAMP SWITCH

1. Power switch OFF.
2. Disconnect stop lamp switch connector.
3. Check continuity between following terminals of the stop lamp switch.

| Terminals |   | Condition                         | Continuity  |
|-----------|---|-----------------------------------|-------------|
| 1         | 2 | When brake pedal is depressed     | Existed     |
|           |   | When brake pedal is not depressed | Not existed |

Is the inspection result normal?

- YES >> INSPECTION END  
 NO >> Replace stop lamp switch.

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
M  
N  
O  
P

VSP

# CHARGE PULSE SIGNAL CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

## CHARGE PULSE SIGNAL CIRCUIT

### Description

INFOID:000000007632000

The VCM outputs the charge pulse signal to the VSP control unit.

### Component Function Check

INFOID:000000007632001

#### 1. CHECK CHARGE PULSE INPUT SIGNAL

1. Connect the CONSULT.
2. Select the "DATA MONITOR" for the "VSP" and check the "VCM IN SIG" monitor value.

|  |              |
|--|--------------|
|  | "VCM IN SIG" |
| When charge connector is connected     | : Hi         |
| When charge connector is not connected | : Lo         |

>> INSPECTION END

### Diagnosis Procedure

INFOID:000000007632002

#### 1. CHECK CHARGE PULSE SIGNAL CIRCUIT

1. Power switch OFF.
2. Disconnect VSP control unit connector and VCM connector.
3. Check continuity between VSP control unit harness connector and VCM harness connector.

| VSP control unit |          | VCM       |          | Continuity |
|------------------|----------|-----------|----------|------------|
| Connector        | Terminal | Connector | Terminal |            |
| M47              | 6        | E63       | 88       | Existed    |

4. Check continuity between VSP control unit harness connector and ground.

| VSP control unit |          | Ground | Continuity  |
|------------------|----------|--------|-------------|
| Connector        | Terminal |        |             |
| M47              | 6        |        | Not existed |

Is the inspection result normal?

- YES >> GO TO 2.  
NO >> Repair the harnesses or connector.



#### 2. CHECK CHARGE PULSE INPUT SIGNAL

1. Connect VSP control unit and stop lamp switch connector.
2. Power switch ON.
3. Check voltage between VSP control unit harness connector and ground.

| Terminals        |          | Condition | Voltage (Approx.) |
|------------------|----------|-----------|-------------------|
| (+)              |          |           |                   |
| VSP control unit |          |           |                   |
| Connector        | Terminal |           |                   |
|                  |          |           |                   |

# CHARGE PULSE SIGNAL CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

|     |   |        |  |  |
|-----|---|--------|--|--|
| M47 | 6 | Ground | When charge connector connected  |  <p>JSMIA0566GB</p> |
|     |   |        | <ul style="list-style-type: none"> <li>• When power switch OFF</li> <li>• When charge is accepted</li> </ul> |  <p>JSMIA0566GB</p> |
|     |   |        | Other than the above   | 0 V  |

Is the inspection result normal?

- YES >> Replace the VSP control unit. Refer to [VSP-54, "Removal and Installation"](#).  
 NO >> Perform "Self Diagnosis Result" of VCM.

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
M  
N  
O  
P

VSP

# POWER SWITCH SIGNAL CIRCUIT

< DTC/CIRCUIT DIAGNOSIS >

## POWER SWITCH SIGNAL CIRCUIT

### Description

INFOID:000000007632003

The power switch outputs the power switch signal to the VSP control unit.

### Component Function Check

INFOID:000000007632004

#### 1. CHECK POWER SWITCH INPUT SIGNAL

1. Connect the CONSULT.
2. Select the "DATA MONITOR" for the "VSP" and check the "PUSH SW" monitor value.

|                                  |           |
|----------------------------------|-----------|
|                                  | "PUSH SW" |
| When power switch is pressed     | : On      |
| When power switch is not pressed | : Off     |

>> INSPECTION END

### Diagnosis Procedure

INFOID:000000007632005

#### 1. CHECK POWER SWITCH SIGNAL CIRCUIT

1. Power switch OFF.
2. Disconnect VSP control unit and power switch connector.
3. Check continuity between VSP control unit harness connector and power switch harness connector.

| VSP control unit |          | Power SW  |          | Continuity |
|------------------|----------|-----------|----------|------------|
| Connector        | Terminal | Connector | Terminal |            |
| M47              | 3        | M25       | 8        | Existed    |

4. Check continuity between VSP control unit harness connector and ground.

| VSP control unit |          | Ground | Continuity  |
|------------------|----------|--------|-------------|
| Connector        | Terminal |        |             |
| M47              | 3        |        | Not existed |

5. Check continuity between power switch harness connector and ground.

| Power SW  |          | Ground | Continuity |
|-----------|----------|--------|------------|
| Connector | Terminal |        |            |
| M25       | 4        |        | Existed    |

Is the inspection result normal?

- YES >> GO TO 2.  
NO >> Repair harness or connector.

#### 2. CHECK POWER SWITCH INPUT SIGNAL

1. Connect VSP control unit and power switch connector.
2. Power switch ON.
3. Check voltage between VSP control unit harness connector and ground.

| Terminal         |          | Condition | Voltage (Approx.) |
|------------------|----------|-----------|-------------------|
| (+)              | (-)      |           |                   |
| VSP control unit |          |           |                   |
| Connector        | Terminal |           |                   |

# POWER SWITCH SIGNAL CIRCUIT

## < DTC/CIRCUIT DIAGNOSIS >

|     |   |        |                                  |      |
|-----|---|--------|----------------------------------|------|
| M47 | 3 | Ground | When power switch is pressed     | 0 V  |
|     |   |        | When power switch is not pressed | 12 V |

Is the inspection result normal?

- YES >> Replace VSP control unit. Refer to [VSP-56, "Removal and Installation"](#).  
NO >> Refer to [VSP-45, "Component Inspection"](#).

## Component Inspection

INFOID:000000007632006

### 1. CHECK POWER SWITCH

1. Power switch OFF.
2. Disconnect power switch connector.
3. Check continuity between following terminals of the power switch.

| Terminals |   | Condition                        | Continuity  |
|-----------|---|----------------------------------|-------------|
| 8         | 4 | When power switch is pressed     | Existed     |
|           |   | When power switch is not pressed | Not existed |

Is the inspection result normal?

- YES >> INSPECTION END  
NO >> Replace power switch.

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
M  
N  
O  
P

VSP

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SYSTEM SYMPTOMS

< SYMPTOM DIAGNOSIS >

## SYMPTOM DIAGNOSIS

### APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SYSTEM SYMPTOMS

#### Symptom Table

INFOID:000000007632007

| Symptoms  | Check items   | Possible malfunction location/Action to take  |
|---|---|---|
| No sound from VSP speaker                               | <ul style="list-style-type: none"> <li>Input signals from combination meter are normal.</li> <li>VSP sound and charge sounds do not sound.</li> </ul>                         | <ul style="list-style-type: none"> <li>VSP speaker</li> <li>VSP speaker signal circuit</li> </ul> Refer to <a href="#">VSP-49, "Diagnosis Procedure"</a> .  |
| No sound from start up sound speaker                    | <ul style="list-style-type: none"> <li>Input signals from combination meter are normal.</li> <li>Power switch operation sound and READY effect sound do not sound.</li> </ul> | <ul style="list-style-type: none"> <li>Start up sound speaker</li> <li>Start up sound speaker signal circuit</li> </ul> Refer to <a href="#">VSP-50, "Diagnosis Procedure"</a> .  |
| Driving start sound does not sound.                     | Driving sound and reverse sound operate.  | Stop lamp switch signal circuit<br>Refer to <a href="#">VSP-48, "Diagnosis Procedure"</a> .   |
| Power switch operation sound does not sound.            | READY effect sound occurs.  | Power switch signal circuit<br>Refer to <a href="#">VSP-52, "Diagnosis Procedure"</a> .   |
| Charge sound does not sound.                            | Plug-in detection sound and charge acceptance sound do not sound.   | Charge pulse signal circuit<br>Refer to <a href="#">VSP-51, "Diagnosis Procedure"</a>   |
| VSP warning lamp does not turn ON or does not turn OFF. | —   | <ul style="list-style-type: none"> <li>VSP warning lamp</li> <li>VSP warning lamp signal circuit</li> </ul> Refer to <a href="#">VSP-47, "Diagnosis Procedure"</a> . <ul style="list-style-type: none"> <li>VSP control unit</li> </ul> |

# THE APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) WARNING LAMP DOES NOT TURN ON OR OFF

< SYMPTOM DIAGNOSIS >

## THE APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) WARNING LAMP DOES NOT TURN ON OR OFF

### Description

INFOID:000000007632008

- VSP warning lamp does not turn ON.
- VSP warning lamp does not turn OFF except when:
  - Communication error occurs.

### Diagnosis Procedure

INFOID:000000007632009

#### 1. CHECK VSP WARNING LAMP OPERATION

1. Connect CONSULT and select "ACTIVE TEST" for "VSP" to check the operation of "VSP IND". Refer to [VSP-38, "Component Function Check"](#).

Is the inspection result normal?

- YES >> Replace VSP control unit. Refer to [VSP-54, "Removal and Installation"](#).
- NO >> GO TO 2.

#### 2. CHECK FUSE

Check fuse. Refer to [VSP-38, "Diagnosis Procedure"](#).

Is the inspection result normal?

- YES >> GO TO 3.
- NO >> Replace the fuse after repairing the applicable circuit.

#### 3. CHECK VSP WARNING LAMP POWER SUPPLY CIRCUIT

Check VSP warning lamp power supply circuit. Refer to [VSP-38, "Diagnosis Procedure"](#).

Is the inspection result normal?

- YES >> GO TO 4.
- NO >> Repair harness or connector.

#### 4. CHECK VSP WARNING LAMP SIGNAL CIRCUIT

Check VSP warning lamp signal circuit. Refer to [VSP-38, "Diagnosis Procedure"](#).

Is the inspection result normal?

- YES >> Replace VSP warning lamp.
- NO >> Repair harness or connector.

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
M  
N  
O  
P

VSP

# THE DRIVING SOUND DOES NOT SOUND

< SYMPTOM DIAGNOSIS >

---

## THE DRIVING SOUND DOES NOT SOUND

### Description

INFOID:000000007632012

The driving start sound does not operate when the selector lever is in the “D” position and the brake pedal is released.

**NOTE:**

The driving sound and reverse sound operate.

### Diagnosis Procedure

INFOID:000000007632013

#### 1. CHECK STOP LAMP SWITCH INPUT SIGNAL

---

1. Connect the CONSULT.
2. Check the stop lamp switch input signal. Refer to [VSP-40, "Component Function Check"](#).

Is the inspection result normal?

- YES >> Replace the VSP control unit. Refer to [VSP-54, "Removal and Installation"](#).  
NO >> GO TO 2.

#### 2. CHECK STOP LAMP SWITCH SIGNAL CIRCUIT

---

Check the stop lamp switch signal circuit. Refer to [VSP-40, "Diagnosis Procedure"](#).

Is the inspection result normal?

- YES >> GO TO 3.  
NO >> Repair harness or connector.

#### 3. CHECK STOP LAMP SWITCH

---

Check stop lamp switch. Refer to [VSP-41, "Component Inspection"](#).

Is the inspection result normal?

- YES >> Replace the VSP control unit. Refer to [VSP-54, "Removal and Installation"](#).  
NO >> Replace stop lamp switch.



# THE APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SPEAKER DOES NOT SOUND

< SYMPTOM DIAGNOSIS >

## THE APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SPEAKER DOES NOT SOUND

### Description

INFOID:000000007632014

The driving start sound, driving sound, reverse sound, and charge sound all do not operate.

### Diagnosis Procedure

INFOID:000000007632015

#### 1. CHECK VSP SPEAKER OPERATION

1. Connect the CONSULT.
2. Select "VSP SP" of "ACTIVE TEST"
3. Check the VSP speaker operation. Refer to [VSP-34. "Component Function Check"](#).

Is the inspection result normal?

- YES >> Replace the VSP control unit. Refer to [VSP-54. "Removal and Installation"](#).  
NO >> GO TO 2.

#### 2. CHECK VSP SPEAKER SIGNAL CIRCUIT

Check VSP speaker signal circuit. Refer to [VSP-34. "Diagnosis Procedure"](#).

Is the inspection result normal?

- YES >> Replace the VSP speaker. Refer to [VSP-56. "Removal and Installation"](#).  
NO >> Repair harness or connector.

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
M  
N  
O  
P

VSP

# THE START UP SOUND SPEAKER DOES NOT SOUND

< SYMPTOM DIAGNOSIS >

---

## THE START UP SOUND SPEAKER DOES NOT SOUND

### Description

INFOID:000000007632016

The start up sound do not sound.

### Diagnosis Procedure

INFOID:000000007632017

#### 1.CHECK START UP SOUND SPEAKER OPERATION

---

1. Connect the CONSULT.
2. Select "START UP SOUND SP" of "ACTIVE TEST"
3. Check the start up sound speaker operation. Refer to [VSP-36. "Component Function Check"](#).

Is the inspection result normal?

- YES >> Replace the VSP control unit. Refer to [VSP-54. "Removal and Installation"](#).  
NO >> GO TO 2.

#### 2.CHECK START UP SOUND SPEAKER SIGNAL CIRCUIT

---

Check start up sound signal circuit. Refer to [VSP-36. "Diagnosis Procedure"](#).

Is the inspection result normal?

- YES >> Replace the start up sound speaker. Refer to [VSP-55. "Removal and Installation"](#).  
NO >> Repair harness or connector.

# THE CHARGE SOUND DOES NOT SOUND

< SYMPTOM DIAGNOSIS >

## THE CHARGE SOUND DOES NOT SOUND

### Description

INFOID:000000007632018

- The plug-in detection sound does not sound when the charge connector is correctly connected.
- The charge acceptance sound does not sound when the charge is accepted.

#### NOTE:

During quick charge, the plug-in detection sound does not operate.

### Diagnosis Procedure

INFOID:000000007632019

#### 1.CHECK CHARGE PULSE INPUT SIGNAL

1. Connect the CONSULT.
2. Check the charge pulse input signal. Refer to [VSP-42, "Component Function Check"](#).

#### Is the inspection result normal?

- YES >> Replace the VSP control unit. Refer to [VSP-54, "Removal and Installation"](#).  
NO >> GO TO 2.

#### 2.CHECK CHARGE PULSE SIGNAL CIRCUIT

Check charge pulse signal circuit. Refer to [VSP-42, "Diagnosis Procedure"](#).

#### Is the inspection result normal?

- YES >> Replace the VSP control unit. Refer to [VSP-54, "Removal and Installation"](#).  
NO >> GO TO 3.

#### 3.PERFORM SELF-DIAGNOSIS OF VCM

Perform "Self Diagnostic Result" of "VCM", and repair or replace malfunctioning parts.

>> Refer to [EVC-55, "CONSULT Function"](#).

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
M  
N  
O  
P

VSP

# THE POWER SWITCH OPERATION SOUND DOES NOT SOUND

< SYMPTOM DIAGNOSIS >

---

## THE POWER SWITCH OPERATION SOUND DOES NOT SOUND

### Description

INFOID:000000007632020

The power switch operation sound does not sound when the power switch is operated.

### Diagnosis Procedure

INFOID:000000007632021

#### 1. CHECK POWER SWITCH INPUT SIGNAL

---

1. Connect the CONSULT.
2. Check the power switch input signal. Refer to [VSP-44, "Component Function Check"](#).

Is the inspection result normal?

- YES >> Replace the VSP control unit. Refer to [VSP-54, "Removal and Installation"](#).
- NO >> GO TO 2.

#### 2. CHECK POWER SWITCH SIGNAL CIRCUIT

---

Check power switch signal circuit. Refer to [VSP-44, "Diagnosis Procedure"](#).

Is the inspection result normal?

- YES >> GO TO 3.
- NO >> Repair harness or connector.

#### 3. CHECK POWER SWITCH

---

Check power switch. Refer to [VSP-45, "Component Inspection"](#).

Is the inspection result normal?

- YES >> Replace the VSP control unit. Refer to [VSP-54, "Removal and Installation"](#).
- NO >> Replace power switch.

# NORMAL OPERATING CONDITION

< SYMPTOM DIAGNOSIS >

## NORMAL OPERATING CONDITION

### APPROACHING VEHICLE SOUND FOR PEDESTRIANS(VSP) SYSTEM

A

### APPROACHING VEHICLE SOUND FOR PEDESTRIANS(VSP) SYSTEM : Description

B

INFOID:000000007632022

- The VSP during forward driving fades out and stops operating when the vehicle stops [vehicle speed 0 km/h (0 MPH) is detected].
- The VSP during reverse driving continues to operate when the vehicle is stopped.

C

### START UP SOUND SYSTEM

### START UP SOUND SYSTEM : Description

D

INFOID:000000007632023

The power switch operation sound may not be able to respond normally if the power switch is pressed quickly.

### CHARGE SOUND SYSTEM

E

### CHARGE SOUND SYSTEM : Description

F

INFOID:000000007632024

- The charge sound system operates when the power switch is OFF.
- During quick charge, the plug-in detection sound does not operate.

G

H

I

J

K

VSP

M

N

O

P

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) CONTROL UNIT

< REMOVAL AND INSTALLATION >

## REMOVAL AND INSTALLATION


### APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) CONTROL UNIT

#### Removal and Installation

INFOID:000000007632025

#### REMOVAL

1. Remove the glove box cover assembly. Refer to [JP-14, "Removal and Installation"](#).
2. Remove the VSP control unit connector.
3. Remove screw (A), and then remove the VSP control unit (1).



#### INSTALLATION

Install in the reverse order of removal.

# START UP SOUND SPEAKER

< REMOVAL AND INSTALLATION >


## START UP SOUND SPEAKER

### Removal and Installation

INFOID:000000007632026

#### REMOVAL

1. Remove the instrument lower panel LH. Refer to [IP-14. "Removal and Installation"](#).
2. Remove screws (A), and then remove the start up sound speaker (1).



#### INSTALLATION

Install in the reverse order of removal.

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
M  
N  
O  
P

VSP

# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SPEAKER


< REMOVAL AND INSTALLATION >

## APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) SPEAKER

Exploded View


INFOID:000000007632027

DISASSEMBLY



1. Bracket

2. VSP speaker


 : N·m (kg·m, ft·lb)

## Removal and Installation

INFOID:000000007632028

### REMOVAL

1. Remove the front bumper. Refer to [EXT-13, "Removal and Installation"](#).
2. Remove the VSP speaker connector.
3. Remove bolts (A), and then remove the VSP speaker (1).



### INSTALLATION

Install in the reverse order of removal.

### Disassembly and Assembly

INFOID:000000007632029

### DISASSEMBLY

Remove screws, and then remove bracket.

### ASSEMBLY

Assemble in the reverse order of disassembly.



# APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) OFF SWITCH


< REMOVAL AND INSTALLATION >

## APPROACHING VEHICLE SOUND FOR PEDESTRIANS (VSP) OFF SWITCH

Exploded View

INFOID:000000007632030

### REMOVAL




1. VSP OFF switch
2. Switch assembly

### Removal and Installation

INFOID:000000007632031

#### REMOVAL

1. Remove the instrument lower panel LH. Refer to [IP-14. "Removal and Installation"](#).
2. Remove screws (A), and then switch assembly (1).



3. Disengage the pawls to remove the VSP OFF switch.

#### INSTALLATION

Install in the reverse order of removal.